

19" Industrial Cabinet

RS-Series Industrial Rugged Server

- Loading weight : 1500kgs
- Up to 48U Height

Two Open Side Door

Side View

Side Door Open

Top Inside

Inside

Available Color :

Features

- DIY Design, full steel construction with two open side door.
- 24" deep to accommodate deeper servers.
- Unique multifold removable standing rails Provide many internal mounting surfaces and mounting points.
- Locking, full-mesh, removable front and rear door provide ventilation
- 19" standard installation with adjustable dimension.
- Exquisite design with precision measurement and craftsmanship.

PRODUCTION REQUIREMENT

- Main material
Frames: SPCC 2.0 mm
Removable standing rails: SPCC 2.0 mm
Door & side panels: SPCC 1.2 mm
- Comply with: ANSI/EIA RS-310-D、IEC297-2、DIN41494, PART1, PART7 standard.
- Degree of protection – IP20

DATA AFTER TEST

- Maximum loading weight: 1500kg
- Surface coating thickness: 75-85um
- Powder coating surface hardness: 2H

Top Four Cooling Fan

Top Side

Streamlined mesh hole steel front door for best air ventilation

Specification

CODE ORDER	U	EXTER HEIGHT	EXTERIOR WIDTH	EXTERIOR DEPTH
MS-RS6032	32U	1520	600	1055
MS-RS6132	32U	1520	600	1155
MS-RS6037	36U	1743	600	1055
MS-RS6137	36U	1743	600	1155
MS-RS6042	42U	1965	600	1055
MS-RS6142	42U	1965	600	1155
MS-RS6045	45U	2099	600	1055
MS-RS6145	45U	2099	600	1155
MS-RS6047	48U	2232	600	1055
MS-RS6147	48U	2232	600	1155