





**HPL FINISH FS800**  
**STEEL RIASED FLOOR**

**Panel structure** Full steel, independent four corners support structure. Lower panel is ST14 stretched plate, surface plane is SPCC hard steel painted with conductive antistatic epoxy resin. Foaming cement infilled. Lock hole in four corners.

**Advantage** High dimensional precision, strong loadability And shockproof. Adjustable height for pedestal, assembly agility, large wire, good exchangeability. High recycled.



TYPE		FS800
Panel Size		600*600*35mm
Concentrated Load	N	3550
	KG	363
Impact load /N		536
Ultimate Load /N		11550
Uniform Load N		1780
Rolling Load /N	10times	3560
	10000times	2670
Reaction to Fire		A1
Weight per Panel(KG)		15
		Flat Pedestal: FFH=100mm, Tubethickness=1.2mm, Tube diamater=35mm, Bottom size:95*95mm
		Stringer: 570*35*21mm, tube thickness=1.2mm



**MATCH IN ONE SQM :**

- PANEL 2.78PCS
- PEDESTAL 3.3PCS
- SCREW 11.2PCS

20FT CONTAINERCAPACITY:544M2

**Application:** 5A class office building and occasions which require overhead and large wires. Paving carpet, PVC etc for elegant appearance.

